


LED TECHNOLOGY

**5400 sqm**

Illuminated area

Self-sufficient engine powered unit



Operation: **ENGINE**  
Engine Kubota D1105

**X-BOX**  
6X320W 48V LED - 8,5M

# X-BOX


6X320W 48V LED - 8,5M



## FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- **Standard light sensor for machine power on and off**
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions, up to 22 units per truck**
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Digital control panel and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- **Fully bunded tank, 110%**
- Certified wind stability up to 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization


**LOW**   
reduced  
transport costs

**RUNNING TIME**  
 220 litres tank  
**137h**  
Low fuel consumption

**NOISE**   
level 65 dB(A) at 7m

**5400** sqm  
illuminated area 

  
VERY COMPACT dimensions

**22 units**  
per truck 

Dimension & weight	Dimension min (mm)		Dimensions max (mm)		Total weight (kg)
	1200x1200x2560 (LxWxH)		2390x2390x8500 (LxWxH)		1060
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated Area (sqm)
	LED	320W	6	67	5400
Mast	Lifting Method	Max Height	Max Wind Speed	Rotation	
	Hydraulic	8,5 m	110 km/h	340°	
Alternator	Model	Rated Output	Voltage	Degree of protection	
	Synchronous	8,5 kVA-50Hz	230V	IP 23	
Engine	Model	rpm	Tank capacity run time	Fuel consumption	
	Kubota D1105	1500	220 L - 137hrs	1,6 l/h	

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.