

HYBRID LINE

power  
and innovation



**98 kVA**  
combined power

**5,5h** run time

remote  
telemetry

designed and created  
for your needs

Designed to provide  
an exceptional level  
of performance  
for every work on site  
ensuring the right  
balance between power  
and ease of use

**MGTP**  
**45000/60TH**

**T-ZERO<sup>PRO</sup>**



more sustainable  
and environmentally  
friendly future

 **TRIME<sup>®</sup>**  
Power Division

# MGTP 45000/60 TH

**T-ZERO<sup>PRO</sup>**



**REDUCTION  
emissions** CO<sub>2</sub>

## APPLICATIONS



## FEATURES

- ✓ MRS 16 controller
- ✓ 5" Touch monitoring display controller
- ✓ Communication-centre device
- ✓ 48V/1000A BMS to protect the batteries
- ✓ 4G/GPS Antenna + Modem
- ✓ **Remote telemetry & management**
- ✓ Auto recharge of the batteries
- ✓ Automatic peak shaving mode
- ✓ Sides forklift pockets & Central lifting hook
- ✓ Lockable control panel
- ✓ Main circuit breaker & Earth leakage relay
- ✓ Emergency Stop button
- ✓ Bunded tank
- ✓ 3-way valve for external tank
- ✓ Battery switch

## HYBRID LINE

Code	RP313-45TS9
<b>Dimensions</b>	
L x W x H (mm)	3335x2210x2268
Weight (Kg)	3700
<b>Technical Data</b>	
Continuous power (VA)	45000
Battery pack capacity (Wh)	62259
Capacity available DOD 80% (Wh)	49807
Voltage (V)	230/400
Frequency (Hz)	50
<b>Inverter</b>	
Nominal power (VA)	15000
Q.ty	3
System voltage (V)	48
Max charging current (A)	200
<b>Batteries</b>	
Type	LiFePO4
Q.ty	8
Nominal Voltage (V)	25,6
Nominal Capacity (Ah)	304
Cycle Life DOD 80%	>4000
<b>Engine</b>	
Brand	Kohler
Model	KDI3404TCR
Speed	1500
Cooling system	Water
Emission	Stage V
Fuel Tank (l)	700
<b>Alternator</b>	
Brand	Linz
Model	PRO 22S D/4
Rated output (kVA)	100
Frequency (Hz)	50
Power factor (cos φ)	0,8
<b>Distribution panel</b>	
Inlet Plug	1x 63A-400V
Outlet Sockets	1x 63A-400V
	1x 32A-400V
	1x 16A-230V
<b>Performances</b>	
Running time on batteries (h) 25% load	5,5
Running time on batteries (h) 50% load	3,0
Running time on batteries (h) 75% load	1,5
Recharge time from engine (h)	3,5
<b>Available options</b>	
RSV 32A plug + MPPT solar charger for external solar panels	
Mat heating system for batteries to work in cold ambients	
OptionGen PRO controller c/w remote check & management and CO2-Fuel savings calculator	

**hybrid  
technology**



**easy handling & transportability**



**TRIME®**

Sales Dept. +39 0382 406 252 - [www.trime.it](http://www.trime.it) - [info@trime.it](mailto:info@trime.it)

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.