















FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 1 section galvanized telescopic vertical mast
- Maximum mast height 2 m
- · Manual lifting system
- 80 µm powder coating
- Very compact dimensions for easy handling & transportability, up to 54 units per truck
- · Central lifting eye for effective handling
- Hand trolley
- Light weight for improved manoeuvrability
- Simple, rugged machine design and layout
- Protected electrical cable to avoid damage during tower operation
- On/Off switches
- Easy access for maintenance
- 2 extendable & height adjustable galvanized stabilizers
- Battery pack in AGM TECHNOLOGY
- · Built-in battery recharger


















Dimensions 9 weight	Dimensions min (mm)				Dimensions max(mm)				Total weight (kg)				
Dimensions & weight	598x648x1650 (LxWxH)				1000x664x2000 (LxWxH)				108				
Floodlights	Туре		Power (each)		Floodlights number		r	IP level	Illuminated area (sqm)		Charging time with floodlight off		
	Led		70W		2			65	750		± 10 h		
Mast	Lifting	Lifting method		Max Height		Max Wind Speed				Rotation			
	Manual	Manual		2 m		30 km/h			340°				
Battery	Туре			Power Battery Pack		Running time	Bat	Battery charger		Expected battery cycle		Expected battery life	
	AGM	1		12Vdc 110 Ah		8 h	230V 1Ph Built-in		lt-in	500		9000 h	

