


X-PROTECTION



HYBRID
POWERED





Protected



Security Status



Video Control

X-PROTECTION

Static Security Tower

When looking for an advanced, industry suited, static security tower, look no further than our **X-PROTECTION**

Features and Benefits

Non dressed head ready to support your choice of security/ monitoring equipment

5 m vertical galvanized manual mast for quick and simple erection

22 towers to one truck simplifying transport & storage

Hybrid power pack with high level batteries and back up generator with extremely lower fuel consumption up to 6 months autonomous without refueling (based on 24hrs/days running time)



Your security equipment here not included



Safe store security equipment here



Standard load delivery: **22 towers** per truck

NOTE: Tower is supplied non-dressed, meaning that user must supply & fit their own security monitoring equipment.

Specifications

MAST	
Lifting Method	Manual
Max Mast Height	5 m
Rotation	no
Safety brake	Mechanical

BATTERY	
Type	AGM
Number	4
Power battery pack	24VDC - 400 Ah
Expected battery cycle	500

ENGINE	
Model	Kubota Z482 StageV
Speed	@1500 r.p.m.

DIMENSIONS	
Transport dimensions (mm) LxWxH	1150x1150x2492
Dimensions in operation (mm) LxWxH	2325x2350x6000
Dray weight	1200 kg

ALTERNATOR	
Model	Linz Electric
Rated output	3,5 kVA
Frequency	50Hz
Voltage	220V

RUNNING TIME - Based on 100W of power consumption	
Running Time, only battery	75 hrs
Total running time before refilling	4663 hrs



Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it