designed and created for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use



2x29W+1x13W LED

T-ZEROPRO

450 SQM
Illuminated area

VERY COMPACT dimensions

60h running time



more sustainable and environmentally friendly future





2x29W+1x13W LED



LED TECHNOLOGY

450 SQM Illuminated area

















FEATURES

- Battery Charger 24V 60A (230V 1Ph Built-in)
- Mains Input 230V 16A
- Battery Charger Gauge
- Floodlights Hour meter
- Removable lithium battery Full aluminum body
- Tubular Frame for manual handling
- Multi-directionally adjustable and tiltable floodlights
- 3 section galvanized telescopic vertical mast
- Manual lifting system
- Very compact dimensions for easy handling & transportability, up to 42 units per truck
- Light weight for improved manoeuvrability
- 60hrs running time from battery
- 3hrs recharge





imensions & weight	
Dimensions min (mm)	867x627x1824 (LxWxH)
Dimensions max (mm)	867x627x3120 (LxWxH)
「otal weight (kg)	63
Frame (kg) 28 Battery (kg) 24	Must+floodlight (kg) 11
Floodlights	
Гуре	Led
Power (each)	2x29W+1x13W
-loodlights number	3
P level	65
lluminated area (sqm)	450
1ast	
ifting method	Manual
1ax Height	3120 mm
Max Wind Speed	110 km/h
Battery	
Гуре	LITHIUM
Battery number	1
Power Battery Pack	25,9Vdc 200 Ah
Running time	60 h
Battery charger	230V 1Ph Built-in
Charging time with floodlights off	3 h
expected battery cycle	2000
Expected battery life	60000 h



