## designed and creater for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

X-START

4x320W - LED - 8M

more sustainable and environmentally friendly future



TRATE:X

TRIME



## ENGINE POWERED



4x320W - LED - 8M

9300 sqm Illuminated area







## **APPLICATIONS**











## **FEATURES**

- Multi-directionally adjustable and tiltable floodlights
- Galvanized metalworks
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 80 km/h
- § 5 height adjustable stabilizers
- On board levels for guidance during stabilization



Dimensions & weight	
Dimensions min (mm)	1830x1370x2560 (LxWxH)
Dimensions max (mm)	2320x2570x8000 (LxWxH)
Total weight (kg)	706
Floodlights	<u> </u>
Туре	Led
Power(each)	320W
Floodlights number	4
Illuminated area (sqm)	9300
Mast	
Lifting method	Manual
Max Height	8 m
Rotation	340°
Max Wind Speed	80 km/h
Options	Homologated road trailer
Alternator	
Model	Synchronous
Frequency (Hz)	50
Insulation class	Н
Degree of protection	IP 23
Single phase voltage	3,5kVA - 230V
Auxiliary outlets	1 kVA
Engine	
Model	Kubota Z482*
Fuel	Diesel
r.p.m.	1500
Tank capacity (I)	80
Consumption (I/h)	0,55
Running time	145 h
Noise level dB(A) at 7m	65

 $<sup>^*\,\</sup>text{May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used}$ 





