


LED TECHNOLOGY

1500 sqm

Illuminated area



Operation: **POWER**
Inlet plug 16A - 230V

X-TRIPOD
T-ZERO_{PRO}

X-TRIPOD

T-ZERO^{PRO}



FEATURES

- 4x 75W LED – illumination area 1500 sqm
- LED inclination and orientation - manual adjustment
- Max height 7.0 meters
- 4 section Manual Vertical mast with manual winch
- CEE Outlet socket present on the lighting tower
- 230V-50Hz connection
- Made in aluminium
- Stationary application
- Tripod structure with no.4 stabilizers retractable
- Easy to handle
- Transport Dimension: 630x370x1970 mm (LxWxH)
- Total weight 95 Kg
- Very compact for easily handling and transportability



| Dimension & weight | Dimension min (mm) | | Dimensions max (mm) | | Total weight (kg) |
|--------------------|----------------------|--------------|------------------------|----------------|------------------------|
| | 630x370x1970 (LxWxH) | | 2200x2200x7000 (LxWxH) | | 95 |
| Floodlights | Type | Power (each) | Floodlights number | IP level | Illuminated Area (sqm) |
| | LED | 75W | 4 | 65 | 1500 |
| Mast | Lifting Method | Max Height | | Max Wind Speed | Rotation |
| | Manual | 7,0 m | | 80 km/h | NO |
| Input | Inlet plug | | | | |
| | 16A-230V | | | | |

The company reserves the right to modify the technical specifications, items and design without notice.
The images of the products are indicative for illustrative purposes only.