


T-ZERO^{PRO}

POWER & INNOVATION



REMOTE
telemetry



PEAK
shaving



RENEWABLES
Energy Connection



EASY
handling



BATTERY
technology



SINGLE
phase



LITHIUM
battery



PLUG
& play

MGTP 10000/20 BP LITHIUM 1P

Code **BP376-10MS1**

Features

Outlet socket	2x32A - 230V
Inlet plug	1x125A - 230V
Inverter	1x48V/10000VA
Max. Feed through current	2x100A

Lithium Batteries

Battery	25,6V - 200Ah
Batteries number	4
Battery Pack	51,2 VDC-20 kWh
Expected battery cycle	3500 - 80% DOD

Dimensions & Weight

Dimension	1100 x 1010 x 1070 mm
Weight	447 Kg

Distribution Panel

Outlet	2x32A - 230V
Inlet	1x125A - 230V
Auto start cable connection	Standard
MPPT Solar Charger with RVS Plug	Option

Standard Features

Main circuit breaker & Earth leakage relay
Emergency Stop button
Sides forklift pockets
Lockable control panel
Color Control monitoring display controller
4G GPS antenna & GX GSM module
Remote telemetry
Auto recharge of the BP from generator (when connected)
Automatic peak shaving mode (BP+generator)

Continuous Inverter Output Power

10000 VA

Overload (0,5 sec)

25000 VA

Running Time with Constant Load from Batteries

2500 VA	8.0 h
5000 VA	4.0 h

Recharging time - Power requested

3.5 h	10 kW
-------	-------

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.