


T-ZERO^{PRO}

POWER & INNOVATION



REMOTE
telemetry



PEAK
shaving



RENEWABLES
Energy Connection



EASY
handling



BATTERY
technology



SINGLE
phase



THREE
phase



LITHIUM
battery



PLUG
& play

MGTP 30000/55 BP LITHIUM 3P

Code **BP372-30TS0**

Features

Outlet socket	32A + 63A + 125A 3Ph + Hardwire 16A + 32A 1Ph
Inlet plug	63A + 125A 3Ph + Hardwire
Inverter	3x48V/10000VA
Max. Feed through current	3x100A

Lithium Batteries

Battery	25,6VDC -280Ah
Batteries number	8
Battery Pack	51,2 VDC-57.3 kWh
Expected battery cycle	3500 - 80% DOD

Dimensions & Weight

Dimension	1960 x 1350 x 1520 mm
Weight	1210 Kg

Distribution Panel

Outlet	32A + 63A + 125A 3Ph + Hardwire 16A + 32A 1Ph
Inlet	63A + 125A 3Ph + Hardwire
Auto start cable connection	Standard
MPPT Solar Charger with RVS Plug	Option

Standard Features

Main circuit breaker & Earth leakage relay
Emergency Stop button
Sides forklift pockets
Lockable control panel
Cerbo GX Touch 50 monitoring display controller c/w Cerbo GX communication center
4G GPS antenna & GX GSM module
Remote telemetry

Continuous Inverter Output Power

30000 VA

Overload (0,5 sec)

75000 VA

Running Time with Constant Load from Batteries

2500 VA	18,4 h
5000 VA	9,2 h
10000 VA	4,6 h
150000 VA	3,1 h
20000 VA	2,3 h

Recharging time - Power requested

3.4 h	27.5 kW
-------	---------

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.