


## T-ZERO PRO

### POWER & INNOVATION



HYBRID  
technology



LITHIUM  
battery

**STAGE 5**  
CERTIFIED



YANMAR



1500  
RPM



DIESEL



WATER  
cooled



SINGLE  
phase



THREE  
phase



#### MGTP 15000/20 TH LITHIUM 3P

Code **RP117-10TS4**

#### Features

Outlet socket	16A - 400V 32A - 400V
Inlet plug	32A - 400V
Inverter	3 x 48V/5000VA
Battery charger	10kW

#### Alternator

Model	Linz PRO 18M E/4
Rated output	20kVA
Frequency	50Hz
Voltage	230V
Insulation class	H
Degree of Protection	IP23

#### Engine

Model	YANMAR 4TNV88
Fuel	Diesel
Engine speed	1500rpm
Noise level at 7mt	60dBA
Emissions regulations	STAGE 5

#### Consumption only engine mode

Tank capacity	320lt
Fuel consumption - Running time	5.9l/h - 54.2 hrs

#### Lithium Batteries

Battery	25,6V - 200Ah
Batteries number	4
Battery Pack	51,2VDC-20.5kWh
Expected battery cycle	2500 - 80% DOD

#### Dimensions & Weight

Dimension	1700 x 1066 x 1450 mm
Weight	920Kg

#### ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 3110	Fuel level monitor
ON/OFF switch	Fuel reserve signal lamp
Earth leakage circuit breaker	Battery level indicator
Circuit breaker	Voltage indicator
Emergency stop	

#### Distribution Panel

1x32A-400V EEC inlet plug for battery charging
1x32A-400V EEC outlet socket
1x16A-400V EEC outlet socket

#### Standard Features

Automatic battery switch
Sound proof canopy
Exhaust gas silencer
Built in fuel tank
Bunded tank
Forklift pocket
Central lifting eye
Heavy bump stoppers
3 ways valve for external fuel tank connection

#### Continuous Inverter Output Power

15000VA
---------

#### Overload (0,5 sec)

37500VA
---------

#### Running Time with Constant Load from Batteries

4000W	4.1h
8000W	2.0h
12000W	1.4h

#### Recharging time - Power requested

2.4h	13kW
Max Loading during recharging time	2.6kW

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.