

## **POWER & INNOVATION**



technology







**KOHLER** 













MGTP 30000/60 TH LITHIUM 3P	
Code	RP313-30TS3
Features	
Outlet socket	2 x 32A - 400V 2 x 63A - 400V
Inlet plug	63A - 400V
Inverter	3 x 48V/10000VA
Battery charger	20.2kW

Alternator	
Model	Stamford UCI 224G
Rated output	42kVA
Frequency	50Hz
Voltage	400V
Insulation class	Н
Degree of Protection	IP23

Engine	
Model	KOHLER KDI 2504TCR
Fuel	Diesel
Engine speed	1500rpm
Noise level at 7mt	65dBA
Emissions regulations	STAGE 5

Consumption only engine mode		
Tank capacity	700lt	
Fuel consuption - Running time	8.3l/h – 84.3 hrs	

Lithium Batteries	
Battery	25,6V - 280Ah
Batteries number	8
Battery Pack	51,2VDC-57.3kWh
Expected battery cycle	3500 - 80% DOD
Dimensions & Weight	

Dimensions & Weight		
Dimension	3335 x 2210 x 2268 mm	
Weight	3150Kg	
C1 RII **		
On board control panel equipped with:		

on board control panet equipped	WIGH.
DSE 7310 / COMAP MRS16	Fuel level monitor
ON/OFF switch	Emergency stop
Earth leakage circuit breaker	42
	7, 170

## **Distribution Panel**

2x32A-400V + 2x63A-400V outlet socket 1x63A-400V inlet plug 1x32A RVS inlet plug for additional solar panels

Standard Features	
Main circuit breaker	Spark arrestor
Earth leakage relay	Lockable control panel
Emergency stop	Digital tank float
Built in fuel tank c/w 3 ways valve	4G LTE Router
MG Master safety and control unit for the battery system	Cerbo GX Touch 50 monitoring display controller c/w Cerbo GX communication-centre
Sides Forklift pockets	4G Puck MIMO Omni Antenna
Exhaust gas silencer	Bunded tank with alarm
Soundproof canopy	Central lifting eye

## Continuous Inverter Output Power 30000VA

## Overload (0,5 sec)

75000VA

Running Time with Constant Load from Batteries		
10000W	4.6h	
15000W	3.1h	
20000W	2.35h	

Recharging time - Power rec	quested
3.2h	26.9kW
Max Loading	21.1kW

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.

