

## T-ZERO<sup>PRO</sup>

### POWER & INNOVATION



Kubota



1500  
RPM



WATER  
cooled



DIESEL



SINGLE  
phase



SOLAR HYBRID  
technology



LITHIUM  
battery

**STAGE 5**  
CERTIFIED



#### MGTP 8000/10 THS LITHIUM 1P

Code **RP47-10MS8**

#### Features

Outlet socket	16A - 230V 32A - 230V
Inlet plug	32A - 230V
Inverter	1 x 48V/8000VA
Battery charger	2.2kW

#### Alternator

Model	Linz PRO 18S A/4
Rated output	8kVA
Frequency	50Hz
Voltage	230V
Insulation class	H
Degree of Protection	IP23

#### Engine

Model	KUBOTA D1105
Fuel	Diesel
Engine speed	1500rpm
Noise level at 7mt	60dBA
Emissions regulations	STAGE 5

#### Consumption only engine mode

Tank capacity	200lt
Fuel consumption - Running time	3.44l/h - 58.1 hrs

#### Lithium Batteries

Battery	12,8V-200Ah
Batteries number	4
Battery Pack	51,2VDC-10.2kWh
Expected battery cycle	2500 - 80% DOD

#### Solar Panel

Power	4 x 40W
Type	Monocrystalline
Solar Panel deployment	electric

#### Dimensions & Weight

Dimension	1740 x 1066 x 1510 mm
Weight	1050Kg

#### ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 3110	Fuel level monitor
ON/OFF switch	Fuel reserve signal lamp
Earth leakage circuit breaker	Battery level indicator
Circuit breaker	Voltage indicator
Emergency stop	

#### Distribution Panel

1x 32A 3Ph 230V EEC plug for battery charging
1x 32A 3Ph 230V EEC socket
1x 16A 3Ph 230V EEC socket

#### Standard Features

Automatic battery switch
Sound proof canopy
Exhaust gas silencer
Built in fuel tank
Bunded tank
MPPT Solar charger model 150/35
Forklift pocket
Central lifting eye
Heavy bump stoppers
3 ways valve for external fuel tank connection

#### Continuous Inverter Output Power

8000VA

#### Overload (0,5 sec)

20000VA

#### Running Time with Constant Load from Batteries

1000W	8.2 h
2000W	4.1 h
5000W	1.6 h

#### Recharging time - Power requested

4.7 h	2.9kW
Max Loading during recharging time	3.5kW

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.